

DESCRIPTIONS :

1) ATTENTION ! IMPORTANT!

In order to establish your house quickly and correctly
You need to do concrete slab according to the specifications,
dimensions and diameter we provide by using water balance.
You may share with us high pixel clear picture for the concrete slap to have our comments.

2) RECOMENDED SHAPE OF CONCRETE SLAB



G - 3 cm ALUM
F - 25cm C14 READY-MIXED CONCRATE
E - 8mm IRON CESAN
D - 20 DENSITY STYROPOR (EPS)
C - 2mm NYLON
B - NO 3 (ASTM 3) CRUSHED STONE SIEVE SIZE 22-25mm
A - COMPACTED GROUND

3) ABOUT WATER DRAINAGE LEFT BLANKS

The hatched area should be left empty for waste water
plumping as per dimensions provided.

4) ABOUT CONCRATE SLAB

The dashed line indicates the exact measure of the building.
If concrete slab is provided based on our recommendations and
the cross (diagonal) dimensions then building can be placed perfectly.

The drawings is 50 cm. bigger from building each size to create
the prefabricated concrete plan.

5) DIFFERENT ALTERNATIVES

Based on the building plan, floor concrete beams can be prepared.
For more information please call our technical department.

Minimum concrete slab thickness is 25 cm. It is recommended to reinforce
with iron. Concrete slab must be on compact floor.

* Taralı alana beton dökülmeyerek tesisat için boş bırakılmalıdır.
* Zemin betonu teslim taahhütnamenizi almayı unutmayınız.
* Zemin betonu atılırken dikkat edilmesi gereken hususları içerir broşürü almayı unutmayınız.

Karmod®
PREFABRİKE YAPI TEKNOLOJİLERİ

www.karmod.com

SİPARİŞ İÇİN İLGİLİ PROJEYİ ONAYLAMANIZ GEREKMEKTEDİR.
ÜRETİM BU PROJEYE GÖRE YAPILACAĞINDAN ,
ONAYLANDIKTAN SONRA HERHANGİ BİR DEĞİŞİM YAPILAMAZ.

REV	1	SAYFA.NO	1/1
TARİH	17.01.2019		
ÇİZEN	M.İKBAL AKSAKAL		
KONTROL	M.İKBAL AKSAKAL		
ONAY	ABDULLAH YÜCEER		

NOTLAR		NOTLAR	
P1 PENCERE		K1 DIŞ KAPI	
P2 PENCERE		K2 DIŞ KAPI	100/200
P3 PENCERE	180/180	K3 DIŞ KAPI	90/200
P4 PENCERE	180/120	K4 İÇ KAPI	
P5 PENCERE	80/120	K5 İÇ KAPI	84/200
V1 VASİSTAS		K6 İÇ KAPI	75/200
V2 VASİSTAS	60/40		

BİNA YERİ	KAR YÜKÜ
ISTANBUL	80 kg/m²

TEKNİK ÖZELLİKLER

SİSTEM:	PRES
DUVAR KALINLIĞI DIŞ:	60
DUVAR KALINLIĞI İÇ	100
YÜKSEKLİK	2500

BİNA ADI	MÜŞTERİ ADI
HÜNKAR	KATALOG

BİNA ADEDİ	ALANI	REF.NO
1	149 M? -m²	M.IKBAL AKSAKAL

KARMOD PREFABRİK YAPI TEKNOLOJİLERİ İNŞ. SAN. VE TİC. LTD. ŞTİ . - TÜM HAKLARI SAKLIDIR.